

## Refrigerated display cabinets

- › For chilled display of pastries, sandwiches and drinks
- › Hygienic display in stainless steel
- › Attractive display of food and drink
- › Ideal for self-service
- › Digital thermostat
- › Fast and consistent refrigeration with outstanding air-circulation

# › Gamko refrigerated display cabinets inset & surface-mounted

Gamko manufactures and supplies professional refrigerated display cabinets for inset or surface-mounting on a bar or buffet. These compact display cabinets are plug ready and are perfect for displaying tasty treats, for example, pastries, sandwiches or drinks. Thanks to the high-quality machine unit and the outstanding air circulation, a consistent low temperature is created right throughout the display cabinet. Each display cabinet is fitted with built-in lighting.

Gamko supplies the refrigerated display cabinets in five models according to volume. Two of these models are fitted with a machine unit on the bottom. This makes it possible to inset them into the counter so that their contents can be seen from all 4 glass sides. As standard, the refrigerated display cabinets are fitted with two sliding panes on the serving side and a fixed glass pane on the customer side. The refrigerated display cabinets can be extended on the customer side with sliding panels or acrylic hinged windows to facilitate self-service.



AV/MS111 < 150-litre capacity with 2 sliding panes on the serving side

AV/MS111SF < 2 sliding panes on the serving side and 2 hinged windows on the customer side



> AV/MS131 190-litre capacity with 2 sliding panes on the serving side

> AV/MS131SF 2 sliding panes on the serving side and 2 hinged windows on the customer side

AV/MS131H < 305-litre capacity with 2 sliding panes on the serving side

AV/MS131HSF < 2 sliding panes on the serving side and 3 hinged windows on the customer side



> AV/MU64 135-litre capacity with 2 sliding panes on the serving side

> AV/MU64SF 2 sliding panes on the serving side and 2 hinged windows on the customer side

AV/MU84 < 180-litre capacity with 2 sliding panes on the serving side

AV/MU84SF < 2 sliding panes on the serving side and 2 hinged windows on the customer side



## General characteristics refrigerated display cabinets

- > Plug ready (no separate condensing unit required)
- > Fast and consistent refrigeration
- > Outstanding air circulation
- > Energy-saving thanks to the double glazing and 40mm of insulation (polyurethane)
- > Interior and exterior made of chromium steel AISI 430
- > Fluorescent lighting
- > Height-adjustable feet
- > Height-adjustable wire mesh shelves
- > Fitted as standard with 2 sliding panes on the serving side and a fixed pane on the customer side
- > Option: can be extended by fitting 2 or 3 acrylic hinged windows on the customer side (for self-service)
- > Electronic thermostat with digital display
- > Automatic defrost
- > Temperature: +4° C / +8° C
- > Adjustable temperature range from +2° C to +18° C



ITEM NO. SLIDING PANES & FIXED PANE	ITEM NO. SLIDING PANES & HINGED WINDOWS	FINISH	FITTING	INTERNAL VOLUME	COOLING CAPACITY	POWER CONSUMPTION	TEMPERATURE	DIMENSION W x D x H EXTERNAL **	DIMENSION W x D x H INTERNAL	DIMENSION INSET W x D
AV/MS111	AV/MS111SF	AISI 430	surface mounting	150 litres	271W <sup>①</sup>	245W <sup>①</sup>	+4° C / +8° C	1110 x 510 x 540/550/565mm	770 x 430 x 460mm	-
AV/MS131	AV/MS131SF	AISI 430	surface mounting	190 litres	271W <sup>①</sup>	245W <sup>①</sup>	+4° C / +8° C	1310 x 510 x 540/550/565mm	970 x 430 x 460mm	-
AV/MS131H	AV/MS131HSF	AISI 430	surface mounting	305 litres	587W <sup>①</sup>	445W <sup>①</sup>	+4° C / +8° C	1310 x 510 x 815/825/840mm	970 x 430 x 735mm	-
AV/MU64	AV/MU64SF	AISI 430	inset*	135 litres	271W <sup>①</sup>	245W <sup>①</sup>	+4° C / +8° C	642 x 610 x 782/792/807mm	580 x 530 x 435mm	min. 620 x 530 x 245mm
AV/MU84	AV/MU84SF	AISI 430	inset*	180 litres	271W <sup>①</sup>	245W <sup>①</sup>	+4° C / +8° C	842 x 610 x 782/792/807mm	780 x 530 x 435mm	min. 620 x 530 x 245mm

① Conditions: Te = -5° C | Tc = +45° C | ambient temperature = +25° C

\* Provide adequate ventilation for heat extraction.

\*\* Depth of the cabinet is excluding handgrip, including power-supply-connection. During installation: add 40mm to the overall depth (in conjunction with the appliance's plug) and add 10 mm to the total width.

No rights can be derived from the information as shown in this brochure. Content, technical features and prices subject to change. 01/2015